




Position	Qty.	Description	Single Price
	1	<p>UPS 25-60 130</p>  <p>Note! Product picture may differ from actual product</p> <p>Product No.: 96281476 The pump is of the canned rotor type, i.e. pump and motor form an integral unit without shaft seal and with only two gaskets for sealing. The bearings are lubricated by the pumped liquid. The pump has 3-step speed selector. The pump is characterized by:</p> <ul style="list-style-type: none"> * Ceramic shaft and radial bearings. * Carbon axial bearing. * Stainless steel rotor can and bearing plate. * Corrosion-resistant impeller, Composite, PES/PP. * Cast iron pump housing. <p>The motor is a 1-phase motor. No additional motor protection is required.</p> <p>Liquid: Liquid temperature range: 2 .. 110 °C</p> <p>Technical: TF class: 110 Approvals on nameplate: VDE,GS,CE</p> <p>Materials: Pump housing: Cast iron EN-JL1030 ASTM 30 B Impeller: Composite, PES/PP</p> <p>Installation: Amb. max at 80 dgr C liquid: 40 °C Maximum operating pressure: 10 bar Pipe connection: G 1 1/2 Pressure stage: PN 10 Port-to-port length: 130 mm \:</p> <p>Electrical data: Power input in speed 1: 50 W Power input in speed 2: 60 W Max. power input: 70 W Mains frequency: 50 Hz</p>	On request

Position	Qty.	Description	Single Price
		Rated voltage: 1 x 230 V Current in speed 1: 0.22 A Current in speed 2: 0.27 A Max. current: 0.3 A Capacitor size - run: 2.5 µF Enclosure class (IEC 34-5): 44 Insulation class (IEC 85): F Others: Net weight: 2.4 kg Gross weight: 2.6 kg Shipping volume: 0.004 m3 Energy label: C	

96281476 UPS 25-60 130 50 Hz

